

INPUT DATA (DC)		M250-60-2LL-S22/S23/S24	
Recommended input power (STC)	210 - 300 W		
Maximum input DC voltage	48 V		
Peak power tracking voltage	27 V - 39 V		
Operating range	16 V - 48 V		
Min/Max start voltage	22 V / 48 V		
Max DC short circuit current	15 A		
Max input current	9.8 A		
OUTPUT DATA (AC)		@208 VAC	@240 VAC
Peak output power	250 W	250 W	
Rated (continuous) output power	240 W	240 W	
Nominal output current	1.15 A (A rms at nominal duration)	1.0 A (A rms at nominal duration)	
Nominal voltage/range	208 V / 183-229 V	240 V / 211-264 V	
Nominal frequency/range	60.0 / 57-61 Hz	60.0 / 57-61 Hz	
Extended frequency range*	57-62.5 Hz	57-62.5 Hz	
Power factor	>0.95	>0.95	
Maximum units per 20 A branch circuit	24 (three phase)	16 (single phase)	
Maximum output fault current	850 mA rms for 6 cycles	850 mA rms for 6 cycles	
EFFICIENCY			
CEC weighted efficiency, 240 VAC	96.5%		
CEC weighted efficiency, 208 VAC	96.0%		
Peak inverter efficiency	96.5%		
Static MPPT efficiency (weighted, reference EN50530)	99.4 %		
Night time power consumption	65 mW max		
MECHANICAL DATA			
Ambient temperature range	-40°C to +65°C		
Operating temperature range (internal)	-40°C to +85°C		
Dimensions (WxHxD)	171 mm x 173 mm x 30 mm (without mounting bracket)		
Weight	2.0 kg		
Cooling	Natural convection - No fans		
Enclosure environmental rating	Outdoor - NEMA 6		
FEATURES			
Compatibility	Compatible with 60-cell PV modules.		
Communication	Power line		
Integrated ground	The DC circuit meets the requirements for ungrounded PV arrays in NEC 690.35. Equipment ground is provided in the Engage Cable. No additional GEC or ground is required.		
Monitoring	Free lifetime monitoring via Enlighten software		
Compliance	UL1741/IEEE1547, FCC Part 15 Class B, CAN/CSA-C22.2 NO. 0-M91, 0.4-04, and 107.1-01		

* Frequency ranges can be extended beyond nominal if required by the utility

To learn more about Enphase Microinverter technology, visit enphase.com

