



SPLIT-SYSTEM HEAT PUMP

<G>



MODEL MXZ-5C42NAHZ

SERVICE REF. MXZ-5C42NAHZ

UNIT SUPPLY	VOLTS	PHASE	Hz	MAX.VOLTAGE	<u>253</u>
	<u>208/230</u>	<u>1</u>	<u>60</u>	MIN.VOLTAGE	<u>198</u>

APPROVED FOR HACR BREAKERS OR TIME DELAY FUSES.

BREAKER 50 AMPS

MAX.FUSE 52 AMPS

MIN.CIRCUIT AMPACITY 42

FAN MOTOR	F.L.A.	W(OUTPUT)
	<u>0.4+0.4</u>	<u>86+86</u>

COMPRESSOR	R.L.A.	L.R.A.
	<u>19.0</u>	<u>22.0</u>

REFRIGERANT R410A

FACTORY CHARGED 4.8 kg/ 10 LBS. 9 OZ. (0 m/ 0 FT.)

INSTALLER TO MARK : TOTAL CHARGE _____ LBS. _____ OZ.

DESIGN PRESSURES 4.15 MPa / 601 PSIG HI SIDE
2.21 MPa / 320 PSIG LO SIDE

*SUITABLE FOR OUTDOOR INSTALLATION.

WEIGHT 125 kg/ 276 LBS.

SERIAL NO. 5YU01570A

MITSUBISHI ELECTRIC CORPORATION
MADE IN JAPAN

DWG. NO. BH79B698G52

