



ATTIC CARD

THIS IS GREENFIBER® ALL BORATE LOOSE FILL FORMULA INSULATION

Application Coverage Chart			30 lbs (13.6 kg)			INS735	
R-Value at 75° F Mean Temp. Valor de resistencia térmica (valor R) a 75 F de temperatura media	Minimum Thickness (inches) Espesor mínimo (en pulgadas)		Net Coverage (no adjustment for framing) Cubertura neta (sin compensación para el estructura)			Net Coverage (adjusted for 2" x 6" framing on 16" centers) Cobertura neta (con compensación para una estructura de 2" x 6" en centros de 16")	
	Initial Installed Thickness Espesor inicial instalado	Settled Thickness Espesor asentado	Maximum Sq. Ft. per Bag Pies cuadrados máximos por bolsa	Minimum Bags per 1,000 Sq. Ft. Cantidad mínima de bolsas por 1,000 pies cuadrados	Minimum Weight per Sq. Ft. Peso mínimo por pie cuadrado	Maximum Sq. Ft. per Bag Pies cuadrados máximos por bolsa	Minimum Bags per 1,000 Sq. Ft. Cantidad mínima de bolsas por 1,000 pies cuadrados
11	3.24	3.01	89.0	11.2	0.337	98.2	10.2
13	3.85	3.58	73.7	13.6	0.407	81.3	12.3
19	5.65	5.25	48.0	20.8	0.625	52.8	18.9
22	6.54	6.08	40.5	24.7	0.740	44.0	22.7
26	7.72	7.18	33.4	29.9	0.898	35.8	27.9
30	8.89	8.27	28.2	35.4	1.062	30.0	33.3
32	9.47	8.81	26.1	38.3	1.15	27.6	36.2
38	11.20	10.42	21.3	46.9	1.41	22.3	44.8
40	11.77	10.95	20.0	50.0	1.50	20.9	47.8
44	12.91	12.01	17.9	55.9	1.68	18.6	53.8
48	14.05	13.07	16.0	62.5	1.88	16.6	60.2
49	14.33	13.33	15.6	64.1	1.92	16.2	61.7
50	14.62	13.60	15.2	65.8	1.98	15.7	63.7
60	17.44	16.22	12.0	83.3	2.49	12.4	80.6

THE ABOVE COVERAGE CHART IS BASED ON A NOMINAL BAG WEIGHT OF 30 LBS USING A VOLUMATIC III, 3rd GEAR AND 8" GATE. THE CHART IS BASED ON SETTLED THICKNESS AND IS FOR ESTIMATING PURPOSES ONLY. JOB CONDITIONS, APPLICATION TECHNIQUES, EQUIPMENT, AND SETTINGS CAN INFLUENCE ACTUAL COVERAGE. ACTUAL COVERAGE MAY VARY BASED ON CONDITIONS AND IS NOT GUARANTEED BY THE MANUFACTURER. DO NOT EXCEED MAXIMUM SQUARE FEET COVERAGE PER BAG. THE APPLICATOR MUST INSTALL BOTH THE MINIMUM NUMBER OF BAGS PER 1000 SQ. FT. AND THE MINIMUM INSTALLED THICKNESS TO INSURE THE STATED R-VALUE HAS BEEN REACHED. FAILURE TO MEET BOTH THESE REQUIREMENTS MAY PREVENT THE ACHIEVEMENT OF THE SPECIFIED R-VALUE. THE INSTALLED MOISTURE CONTENT MUST BE BETWEEN 16% AND 25% IN ATTIC APPLICATIONS. THIS COVERAGE CHART DOES NOT APPLY TO DRY LOOSE-FILL ATTIC/FLOOR APPLICATIONS. MINIMUM NET WEIGHT IS 28.5 LBS.

Spray Applied Sidewall Applications (2.7 pcf minimum installed density) 30 lbs. (13.6 kg) INS735					
Thermal Resistance (R value) Resistencia térmica (R)	Framin Estructura	Installed Thickness (inches) Espesor instalado (pulgadas)	Minimum Wt. Per Square Foot lb/ft ² Peso mínimo por pie cuadrado lb/ft ²	Maximum Coverage Per Bag (Adjusted for Framing) ft ² /Bag Cobertura máxima por bolsa (con compensación para la estructura)ft ² /Bag	
				(16" oc)	(24" oc)
13	2x4	3.5	0.79	42.0	40.6
21	2x6	5.5	1.24	26.8	25.9

THIS COVERAGE CHART IS BASED ON THE VOLUMATIC III, 2ND GEAR, 6" GATE. THE INSTALLED MOISTURE CONTENT MUST BE BETWEEN 25% AND 35% AS MEASURED BY A HAND HELD MOISTURE METER. DO NOT COVER THE INSULATION UNTIL THE INSULATION MOISTURE CONTENT, MEASURED AND DOCUMENTED AFTER A MINIMUM PERIOD OF 24 HRS FROM THE TIME OF INSTALLATION, REACHES 25% OR LESS IN ACCORDANCE WITH GREENFIBER'S WALLSPRAY MANUAL. INSTALL DRY DENSE PACK INS735 INSULATION IN ALL EXTERIOR WALL SECTIONS WHERE ADDED VAPOR IMPEDIMENTS, SUCH AS CABINETS, MIRRORS, TUBS, AND SHOWER ENCLOSURES ARE LOCATED. IF UNSURE WHERE IMPEDIMENTS ARE LOCATED, DRY DENSE PACK THE ENTIRE EXTERIOR WALL SECTIONS. NON-STANDARD OR UNUSUAL WALL CONFIGURATIONS (I.E. OTHER THAN 2X4 AND 2X6 WALLS) CAN AFFECT THERMAL AND SOUND PROPERTIES AND REQUIRE SPECIAL INSTALLATION CONSIDERATIONS. THESE TYPES OF DESIGNS SHOULD BE ANALYZED AND, IF NECESSARY, TESTED PRIOR TO PLAN REVIEW. THIS PRODUCT IS INTENDED FOR WALLSPRAY APPLICATION IN 2X4 AND 2X6 CONSTRUCTION. CONTACT GREENFIBER TECHNICAL REPRESENTATIVES FOR ALL OTHER ASSEMBLIES.

Dry Dense Sidewall Applications (3.5 pcf minimum installed density) 30 lbs. (13.6 kg) INS735					
Thermal Resistance (R value) Resistencia térmica (R)	Framing Estructura	Installed Thickness (inches) Espesor instalado (pulgadas)	Minimum Wt. Per Square Foot lb/ft ² Peso mínimo por pie cuadrado lb/ft ²	Maximum Coverage Per Bag (Adjusted for Framing) ft ² /Bag Cobertura máxima por bolsa (con compensación para la estructura) ft ² /Bag	
				(16" oc)	(24" oc)
13	2x4	3.5	1.02	32.4	31.3
21	2x6	5.5	1.60	20.6	19.9

THIS COVERAGE CHART IS FOR DRY APPLICATIONS ONLY AND IS BASED ON THE KRENDEL KS200, WITH MATERIAL APPLIED DRY.

GreenFiber provides outstanding thermal performance, fire-resistance and sound control. Consisting of up to 85% recycled content, GreenFiber Insulation is specially treated for flame resistance.

R-value means resistance to heat flow - the higher the R-value, the greater the insulation power.

CERTIFICATION:

This insulation has been installed in conformance with the above recommendations, to provide a value of R-_____ using _____ bags of this insulation to cover _____ square feet of area.

Builder's Signature: _____

Company Name: _____

Date: _____

Applicator's Signature: _____

Company Name: _____

Date: _____

FOR MORE INFORMATION CONTACT GREENFIBER:

800.228.0024

greenfiber.info@greenfiber.com

GreenFiber Corporate Office
5500 77 Center Drive, Suite 100
Charlotte NC 28203
www.greenfiber.com

MANUFACTURING LOCATIONS:

Delphos, OH 45833
Debert, Nova Scotia
Norfolk, NE 68701
Chandler, AZ 85043
Salt Lake City, UT 84119
Tampa, FL 33605
Vars, Ontario
Waco, TX 76704
Wilkes-Barre, PA 18702



UL Classified, see complete marking on back of packaging

