

STANDING SEAM METAL ROOF ON
30# SYNTHETIC UNDERLAYMENT ON
5/8" PLYWOOD ROOF SHEATHING

4" (MIN.) SPRAY FOAM INSUL. (R-28)
(R7 PER INCH)

BLOWN-IN-BATT INSUL. (R-32.8)
(4.1 PER INCH)

METAL DRIP EDGE

BEVELED TOP PLATE
(SEE DETAIL ON SHT. 6)

LAP SIDING (4 1/4" EXPOSURE)
ON TYVEK OVER
3/4" PLYWOOD

TEG 1X6 BOARDS (STAINED)
OVER 1X FIRRINGS @ 16" O.C.

PERFORATED METAL STARTER (5")
(CONTINUOUS VENT STRIP)

2X6 EXTERIOR WALL
STUDS @ 16" O.C.

7/16" OSB. PLYWD. SHTG.
2-LAYERS OF 1" RIGID FOAM
(OFFSET & TAPE JOINTS)

1/2" GYPSUM BRD.

R-20 INSULATION
(FOAM SEAL ALL CONST. JOINTS)

48"
(SHTG. TO SHTG.)

FACE BRICK
W/ WEEPS / COVE
3/4" MIN. AIR SPACE

EAVE DETAIL

SCALE: 1/2" = 1'-0"

(AT 'I' JOIST)

