



LG Wall Mounted 5-Zone System - 60,000 BTU Outdoor - 7k + 7k + 7k + 9k + 18k Indoor - 21 SEER



Click to Enlarge Image



Our Price

Shipping Info

Model: L5H60W07070918

\$5,484.00

As low as \$483 / month at 10% APR with [Affirm](#) ⓘ
See how much you qualify for

In-Stock Ships Today, August 10th

Free Shipping

Free Lift Gate Service - [Learn More](#)

Outdoor Unit BTU/h

60,000

Indoor Unit Sizes ⓘ

7k + 7k + 7k + 9k + 18k

High Heating Capacity

No

Add-Ons

Add Lift Gate Service **FREE** [Learn More](#)

FREE: Have 1 installer contact me for a quote. [Learn More](#)

Qty. 1

Add To Cart

Product Description

Reviews

Product Q&A 1

Recommended Accessories

How-To Articles

Manuals

Features

LG's devotion to providing efficient ductless solutions can be seen across the Multi F line. This wall mounted ductless heat pump system pairs a powerful LMU600HV outdoor condenser with LG's Standard Indoor line. An easy installation process and low sound levels mean that this system provides temperature control that doesn't disrupt your home. The well-rounded indoor units feature several convenient operation modes and each includes a wireless remote controller, making it easy for you to enjoy zoned comfort.

Inverter Technology

- LG's multi-zone outdoor condensers are designed with powerful, efficient inverter technology. An electronic expansion valve and a variable speed condenser compressor carefully regulate the refrigerant flow, reducing energy consumption.

Gold Fin Protection

- To ensure the reliability and longevity of the LMU600HV's heat exchanger, LG employs a Gold Fin coating that prevents corrosion and improves durability.

Low Ambient Operations

- Cold temperatures can't slow the Multi F line of outdoor condensers down. This outdoor unit supports cooling operations down to 14

Specifications

General Information

Type	Wall Mounted
Product Line	Multi F MAX
Operating Mode ⓘ 	Cooling + Heating
Number of Zones ⓘ 	5
Indoor Unit Size(s) ⓘ 	6 + 6 + 6 + 9 + 18
DOE Regional Compliance ⓘ 	Nationwide

Performance

Cooling Capacity	45000 BTU
Heating Capacity	51750 BTU
SEER ⓘ 	21.0
EER ⓘ 	12.2
HSPF ⓘ 	11.4
Cooling Power Input	3703 Watts
Heating Power Input	3938 Watts

degrees Fahrenheit and heating operations down to -4 degrees Fahrenheit.

Quiet Design

- Thanks to a brushless direct current fan motor, both the outdoor and indoor units in this system produce less mechanical and electrical noise, allowing them to provide comfort that doesn't disrupt your home.

Air Flow Options

- This unit gives you two options for automating air flow. In swing mode, the unit will rotate through all four air flow directions and with the Chaos Wind feature, it cycles both air flow direction and fan speed.

Self-Cleaning Coil

- These wall mounted indoor units feature self-cleaning heat exchanger coils that automatically remove dirt and moisture. This helps to prevent unpleasant odors and to combat the formation of mold.

Jet Temperature Control

- Getting your Zone Comfortable quickly is no problem thanks to the Jet Cool mode with these indoor units. With the press of a button, your system will operate at maximum output to provide rapid zoned cooling.

Improved Air Quality

- All of LG's wall mounted multi-zone mini split indoor units keep your air clean with a washable anti-fungal filter.

Hot Start

- When the hot start function is enabled on a mini split indoor unit, the fan will not engage until the the indoor coil is up to temperature. This prevents the unit from blowing cold air during heating operations.

Recommended line set sizes for indoor unit connectivity:

- LMN078HVT: 1/4" x 3/8" Line Set (Qty 3)
- LSN090HSV4: 1/4" x 3/8" Line Set
- LSN180HSV4: 1/4" x 1/2" Line Set

A branch box with a 3/8" x 3/4" line set connection is also required. Additional branch boxes and line sets may be required based on your configuration.

Product Includes

- (1) LG - 60k BTU - Outdoor Condenser - For 2-8 Zones ([LMU600HV](#))
- (1) LG 18k BTU Wall Mounted Unit - For Multi or Single-Zone ([LSN180HSV5](#))
- (1) LG 9k BTU Wall Mounted Unit - For Multi or Single-Zone ([LSN090HSV5](#))
- (3) LG 7k BTU Wall Mounted Unit - For Multi-Zone ([LMN079HVT](#))

Product Note

Each indoor unit will include any port adapters necessary for multi-zone installation. This product requires the following accessories for installation:

- **Line Set** - This double insulated tubing transfers refrigerant efficiently between your outdoor condenser and indoor units.
- **Branch Box** - An LG branch box is required to connect this condenser to LG mini split indoor units.
- **Drain Tubing** - Drain tubing facilitates the reliable and effective removal of condensate from your system. It connects your indoor units to drain locations of your choosing.
- **Disconnect Box & Electrical Whip Kit** - The Disconnect Box & Whip Kit provides a safe and simple way to connect your outdoor condenser to your fuse box.
- **Connecting Wire** - This durable, insulated wire provides power to your indoor units from your outdoor condenser.
- **Base Pan Heater** - The base pan heater prevents ice from building up on the outdoor unit. Excessive ice build will lead to performance issues and could damage your unit.
- **Outdoor Condenser Plastic Pad or Wall Bracket** - We recommend outdoor condensers should not be placed directly on the ground. An outdoor condenser pad or wall bracket will

Minimum Outdoor Temperature for Heating	-4 F
---	------

Minimum Outdoor Temperature for Cooling	14 F
---	------

Dimensions

Product Weight	320 Pounds
----------------	------------

Shipping Weight	375 Pounds
-----------------	------------

Certifications

Energy Star Listed	Yes
--------------------	-----

UL Listed	Yes
-----------	-----

ETL Listed	Yes
------------	-----

AHRI Certified	Yes
----------------	-----

ISO Certified	Yes
---------------	-----

AHRI Reference Number	8898928
-----------------------	---------

LMU600HV Specifications

LSN180HSV5 Specifications

LSN090HSV5 Specifications

LMN079HVT Specifications