



COR-A-VENT V-600-T RIDGE VENT

STANDING SEAM METAL ROOF

SIMPSON SDWS .220 X 8" SCREW, 8" O.C.

ALTERNATE BETWEEN 1 X 4 SLATS AND OSB. 2" MIN. PENETRATION INTO SOLID MEMBER

1 x 4 -10' D.F. #2 16" O.C. RUNNING 45 DEG. UP ROOF LINE TO PEAK. 2" MIN. SPACE BETWEEN BOARDS TO ALLOW FOR VENTING

7/16" OSB

GPS RIGID INSULATION, 25 LB DENSITY, 2 LAYER @ 2" EACH, STAGGERED JOINTS. R-5 / INCH. ATTACH USING THERMAL-GRIIP Ci 2" PRONG WASHER W/ GALV. #10 X 5" SCREW, 2' O.C. TAPE ALL SEAMS

WRB

COR-A-VENT S400 SPACER

2 X 10 FACIA

2 X 6 RAFTER TAIL CUT TO 3-1/2" AT EAVE

DENSE PACK CELLULOUS, R 3.6 / INCH @ RAFTERS
 TYVEK OR EQUAL STAPLED TO RAFTERS

**REFER TO S4.0 " ROOF FRAMING PLAN" FOR STRUC. REQ.