



1'-0" MIN.

12  
5

ENGINEERED TRUSSES (150 LB/SF SNOW LOAD) 24" O/C

ARCHITECTURAL SHINGLES - 50-YEAR RATED

30 LB. BUILDING PAPER

GRACE ICE & WATER SHIELD (LOWER 6')

3/4" PLYWOOD

1" x 3 1/2" POLYISO ON TRUSS SIDES

1" x 22 1/2" POLYISO Baffle

OSB SHEATHING TO FULL HEIGHT OF TRUSS HEEL

N-IN  
CLOSE INSUL  
(R-60; NOM. 19" DEEP)

VAPOR BARRIER  
SEAMS & EDGES

5/8" DRYWALL

3/4" KNOTTY PINE T&G

1/2" DRYWALL

R19 FIBERGLASS  
BATT (UNFACED)

2x6 STUDS 24" O/C

2'-6" TRUSS TAILS

FIBER CEMENT BD.

3 1/2" VULCAN  
FIRE-RESISTANT  
CONT. SOFFIT VENT

1" x 6" HORIZ. WESTERN  
RED CEDAR SIDING

1" x 4" FURRING STRIPS

10" x #17 LAG SCREWS  
16" O/C VERTICALLY

3 LAYERS x 2" EPS RIGID FOAM  
(ALL SEAMS STAPLED & TAPE D)

EXTERIOR MEMBRANE

7/16" OSB SHEATHING  
(8d NAILS 6" O/C PANEL  
EDGES; 12" O/C FIELD)

UNFACED R-25  
FIBERGLASS  
INSUL.

FINISHED FLOORING

3/4" SLEEPERS AROUND  
PEX TUBING & THERMOFIN  
PLATES

3/4" OSB T&G SUBFLOOR

1 5/8" x 11 7/8" RIM JOIST (CONT)

11 3/8" TJI 210 JOIST  
@ 19.2" O/C

5" DRYWALL

SUPPORT WIRE  
AS NEEDED