

FINISH ALL TRIM JOINTS WITH  
PAINTABLE SEALANT [S3] WHERE  
JOINTS ARE GREATER THAN 1/16"

FOAM ROD AND SEALANT [S2]  
(AIR AND WATER BARRIER)

INTERIOR WOOD JAMB EXTENSION

SELF-ADHESIVE AIR AND WATER  
BARRIER MEMBRANE [M1]

SILICONE SEALANT HEEL BEAD [S2]  
(AIR AND WATER BARRIER)

PVC WINDOW

FILL VOID WITH SPRAY FOAM INSULATION  
EXCLUDING EXTERIOR SIDE FOR DRAINAGE

FOAM ROD AND SEALANT [S1]

26GA PREFINISHED METAL FLASHING  
WITH #8 PANHEAD SCREW @ 16" O/C,  
EXTEND AT JAMBS.

10%  
SLOPE

SHIM FLASHING TO PERMIT  
INCIDENTAL MOISTURE DRAINAGE

SELF-ADHESIVE AIR BARRIER  
MEMBRANE DETAIL STRIP [M1]

3/4"

MAX 3"

1 1/2"  
MIN

1 1/2"  
MIN

3/4"

WOOD TRIM TO COVER  
SELF-ADHESIVE AIR  
BARRIER MEMBRANE

8±

