

Type text here

QUESTION: (YELLOW HIGHLIGHT)
WILL ADDING 1 1/2" RIGID INSULATION
AND 3/4" PLYWOOD FINISH CREATE A
MOISTURE/CONDENSATION ISSUE
INSIDE THE WALL?
NOTE: THE INTERIOR RIGID
INSULATION ADDED IS INSIDE THE
POLYETHYLENE VAPOR BARRIER

- EXISTING CORRUGATED METAL SIDING
- EXISTING 2X4 HORIZONTAL STRAPPING
- EXISTING 2X6 AND 6X6 WOOD FRAMING
- EXISTING 6" R-19 FIBERGLASS BATT INSULATION
- EXISTING 5 ML CLEAR PLASTIC POLYETHYLENE VAPOR BARRIER STAPLED ON INSIDE FACE OF 2X6 FRAMING
- EXISTING 2X4 HORIZONTAL STRAPPING
- EXISTING 4" CONC. SLAB W/ HYDRONIC RADIANT TUBE HEATING
- EXISTING 4" EPS RIGID FOAM INSULATION W/ 1 1/2" UPTURN AT SLAB EDGE
- EXISTING 2" SAND
- EXISTING 6" STONE
- EXISTING CONCRETE FOOTING WALLS

